EXPORT GATALOGUE EFFEGINE FROM JANUARY 2024

MISGELLANEOUS AND ORIGINAL AGGESSORIES





COLOR TABLE

Standard		RAL 1007	Yellow	A => /40
Optional		RAL 3002	Red	B => /16
Optional		RAL 5015	Blue	C => /25
Optional		RAL 9006	Light gray	D => /36
Main frame is al	ways d	ark grey RAL 70	16	=>/34

NEXION SPA reserves the right to change the specifications of its products at any time without prior notice. The company declines all responsibility in the event of claims deriving from the use of non-original accessories or spare parts with consequent forfeiture of the EC declaration of conformity.



SUMMARY

AUXILIARY WHEEL LIFTERS	4
PARTNER 70	4
NITROGEN GENERATOR	5
N SERIES	5
N 300	5
N 500	5
N 1800	5
OPTIONAL ACCESSORIES FOR SERIE N	6
WHEEL WASHER	8
LS 850	8
OPTIONAL ACCESSORIES FOR LS 850	9
VULCANIZERS SVP1 SVP2 SVP3 SVP4 SVP5 SVP5/L OPTIONAL ACCESSORIES FOR VULCANIZERS	11 11 11 12 12 12 13
TYRE TEST TANKS	14
AL18	14
AL24	14
AIR CONDITIONING SYSTEM DIAGNOSIS AND RECHARGE STATION	15
A/C 1100 SERIES	15
A/C 1105 SERIES	16
A/C 1600 SERIES	17
A/C 1605 SERIES	18
OPTIONAL ACCESSORIES	19



AUXILIARY WHEEL LIFTERS

PARTNER 70

Battery-Operated Wheel Lifter - it helps to easily and safely demount, move and mount the wheels of cars, SUVs and LT vehicles weighting up to 70kg



Code	Electric supply	Description	
8-21120020/64		PARTNER 70	



NITROGEN GENERATOR

N SERIES



Code	Electric supply	Description
0-55401200/16		<i>N 300</i> Nitrogen generator with capacity 3,0 Nm 3/h (3000 lit/h).
0-55401300/16		<i>N 500</i> Nitrogen generator with capacity 5,0 Nm 3/h (5000 lit/h).
0-55401600/16		<i>N 1800</i> Nitrogen generator with capacity 18,0 Nm 3/h (18.000 lit/h).



OPTIONAL ACCESSORIES FOR SERIE N

Image	Description	Code
	WS Cyclonic condensate separator.	8-53600000
	AT Pipes take-up.	8-55600001
	PSG Professional inflating and deflating pistol.	8-55600002
	<i>EC</i> Inflating and deflating pistol, pressure gauge BAR G 1/4"	8-11100362



OPTIONAL ACCESSORIES FOR SERIE N

Image	Description	Code
	EC Inflating and deflating pistol, pressure gauge BAR and PSI G 1/4"	8-51120007
	NT Kit for measuring purity.	8-11600127
	<i>Kit</i> filter cartridges 3-5 Nm3/h.	8-55600023
	<i>Kit</i> filter cartridges 20 Nm3/h.	8-55600024
	<i>Air contamination</i> indicator.	8-55600025



WHEEL WASHER

LS 850



Code	Electric Supply	Description	
0-55400800/34	400V / 3Ph / 50Hz	LS 850 B with steel tank, without heater.	
0-55400700/34	400V / 3Ph / 50Hz	LS 850 P with steel tank and heater.	
0-55401500/34	400V / 3Ph / 50Hz	LS 850 T with stainless steel tank and heater.	



OPTIONAL ACCESSORIES FOR LS 850

Image	Description	Code
x2	RTP kit, replacing kit for drive roller.	8-55600026
x2 Constants	RSA kit , replacing kit for support roller.	8-55600027
	SLR Wheel Lifter.	8-51120005



OPTIONAL ACCESSORIES FOR LS 850

Image	Description	Code	
	Set of granules for filling and replacement (15 kg.).	8-51100063	
	Non-foaming <i>liquid detergent</i> , 10 lt.	8-55600010	
	VSS Ball faucet for water drainage.	8-55600019	
	RCS Elbow fitting for water drainage.	8-55600018	







SVP1





SVP2



Code	Electric Supply	Description	
0-51400310/40	230V/1Ph/50-60Hz	SVP1 with manual lever operated plate clamping	
0-51400320/40	230V/1Ph/50-60Hz	SVP2 With air-operated closingmechanism, to repaire inner tubes and lightweigt tyres	
0-51400330/40	230V/1Ph/50-60Hz	SVP3 Strongly built and easy to use, ideal to repair inner tubes and light weight tyres 600W heating plate.	



VULCANIZERS



SVP4

SVP5

SVP5/L

Code	Electric Supply	Description	
0-51400340/40	230V/1Ph/50-60Hz	SVP4 Vulcanizer with double heating plate airoperated system to close the plates monitored by a pressure governor	
0-51400350/40	230V/1Ph/50-60Hz	SVP5 Vulcanizer with mechanically closed double heating plate.	
0-51400355/40	230V/1Ph/50-60Hz	SVP5/L Vulcanizer with mechanically closed double heating plate. Portable and easy to handle. Complete with 120 minutes timer. Two wide 600 W heating plates.	



OPTIONAL ACCESSORIES FOR VULCANIZERS

Image	Description	Code	
	<i>Support</i> stand	805420833	



TYRE TEST TANKS



Code	Electric Supply	Description	
0-51400200/40		<i>AL18</i> Air-operated with 6/8 bar operating pressure, complete with wheel holder lifting and lowering control. Maximum wheel diameter 800 mm. Maximum wheel width 320 mm.	
0-51410200/40	0-51410200/40 AL24 Complete with air filter, air-operated with 8 bar operating pressure. Maximum wheel diameter 1300 mm. Maximum wheel width 500 mm.		



AIR CONDITIONING SYSTEM DIAGNOSIS AND RECHARGE STATION

A/C 1100 SERIES

AIR CONDITIONING SYSTEM DIAGNOSIS AND RECHARGE STATIONS



Code	Electric Supply	Description	
0-66500201/64	230V/1Ph/50-60Hz	<i>A/C 1100</i> Air Conditioning recharging station, R-134a refrigerant only, manual and automatic functions, recovery-recycle-recharge, hybrid vehicle management, 192x64pixels LCD display, Wi-Fi/BT connection	
0-66500601/64	A/C 1100PAir Conditioning recharging station, R-134a refrigerant only, manual and automatic functions, recovery-recycle-recharge, hybrid vehicles management, 192x64pixels LCD display, Wi-Fi/BT connection, printer included		



A/C 1105 SERIES

AIR CONDITIONING SYSTEM DIAGNOSIS AND RECHARGE STATIONS



Code	Electric Supply	Description
0-66500301/64	230V/1Ph/50-60Hz	A/C 1105 Air Conditioning recharging station, R-1234yf refrigerant only, manual and automatic functions, recovery-recycle-recharge, hybrid vehicles management, 192x64pixels LCD display, Wi-Fi/BT connection
0-66500701/64	A/C 1105P Air Conditioning recharging station, R-1234yf refrigerant only, manual and automatic functions, recovery-recycle-recharge, hybrid vehicle management, 192x64pixels LCD display, Wi-Fi/BT connection, printer included	



A/C 1600 SERIES

AIR CONDITIONING SYSTEM DIAGNOSIS AND RECHARGE STATIONS



Code	Electric Supply	Description	
0-66500401/64	230V/1Ph/50-60Hz	 A/C 1600 Fully automatic Air Conditioning recharging station, R-134a refrigerant only, manual and automatic functions, recovery-recycle-recharge, hybrid vehicles management, 7" 800x480pixels TFT-LCD RBG display , Wi-Fi/BT connection 	
A/C 1600PFully automatic Air Conditioning recharging station, R-134a refrigerant only, manual and automatic functions, recovery-recycle-recharge, hybrid vehicles management, 7" 800x480pixels TFT-LCD RBG display , Wi-Fi/BT connection, printer included			



A/C 1605 SERIES

AIR CONDITIONING SYSTEM DIAGNOSIS AND RECHARGE STATIONS



Code	Electric Supply	Description	
0-66500501/64	230V/1Ph/50-60Hz	A/C 1605 Fully automatic Air Conditioning recharging station, R-1234yf refrigerant only, manual and automatic functions, recovery-recycle-recharge, hybrid vehicles management, 7" 800x480pixels TFT-LCD RBG display, Wi-Fi/BT connection	
0-66500901/64	64A/C 1605PFully automatic Air Conditioning recharging station, R-1234yf refrigerant only, manual and automatic functions, recovery-recycle-recharge, hybrid vehicles management, 7" 800x480pixels TFT-LCD RBG display , Wi-Fi/BT connection, printer included		



OPTIONAL ACCESSORIES FOR AIR CONDITIONING SYSTEM DIAGNOSIS AND RECHARGE STATION

Image	Description	Code	
	<i>High/low</i> pressure pipes kit, L=4,5 mt for, R1234yf refrigerant	8-66500010	
	<i>High/low</i> pressure pipes kit, L=4,5 mt, for R134a refrigerant	8-66500011	
	<i>Leak detector</i> with Nitrogen	8-66500209	
	<i>Leak detector kit</i> including UV lamp and glasses only.	6019000305	



